

46. (Amended) An electro-optical glazing structure comprising:

an electro-optical glazing panel including liquid crystal material interposed between a pair of optically-transparent substrates, said electro-optical glazing panel having an electrically-switchable scattering mode of operation and electrically-switchable transmission mode of operation; and

an optical state switching mechanism for electrically-switching said electro-optical glazing panel into said electrically-switchable scattering mode of operation and into said electrically-switchable transmission mode of operation,

wherein the liquid crystal material comprises a chiral liquid crystal and Ethylene-ethylene Glycol glycol Dimethacrylate-dimethacrylate(EGD) commercially available from Aldrich.

51. (Amended) An electro-optical glazing structure comprising:

an electro-optical glazing panel including liquid crystal material interposed between a pair of optically-transparent substrates, said electro-optical glazing panel having an electrically-switchable scattering mode of operation and electrically-switchable transmission mode of operation; and

an optical state switching mechanism for electrically-switching said electro-optical glazing panel into said electrically-switchable scattering mode of operation and into said electrically-switchable transmission mode of operation,

wherein the liquid crystal material comprises a chiral liquid crystal and a monomer selected from the group consisting of Ethylene-ethylene Glycol-glycol Dimethacrylate-dimethacrylate(EGD), urethane acrylates having a viscosity of about 300 to about 400 centipoise, and epoxies having a viscosity of about 1400 to about 1800 centipoise, UV10, UV15-7 and combinations comprising at least one of the foregoing monomers commercially available from Aldrich and Master Bond.

56. (Amended) An electro-optical glazing structure comprising:

an electro-optical glazing panel including liquid crystal material interposed between a pair of optically-transparent substrates, said electro-optical glazing panel having an electrically-switchable scattering mode of operation and electrically-switchable transmission mode of operation; and

an optical state switching mechanism for electrically-switching said electro-optical glazing panel into said electrically-switchable scattering mode of operation and into said electrically-switchable transmission mode of operation,

wherein the liquid crystal material comprises a PSCT liquid crystal material including a chiral liquid crystal, a monomer and a dichroic dye.

61. (Amended) The electro-optical glazing structure of claim 56, wherein said dichroic dye is an anthraquinone dye selected from the group consisting of D5, D35, D52 and combinations comprising at least one of the foregoing dyes commercially available from EMI.


62. (Amended) An electro-optical glazing structure comprising:

an electro-optical glazing panel including liquid crystal material interposed between a pair of optically-transparent substrates, said electro-optical glazing panel having an electrically-switchable scattering mode of operation and electrically-switchable transmission mode of operation; and

an optical state switching mechanism for electrically-switching said electro-optical glazing panel into said electrically-switchable scattering mode of operation and into said electrically-switchable transmission mode of operation,

wherein the liquid crystal material comprises a chiral liquid crystal, a monomer and a surfactant.

83. (Amended) A liquid crystal material for an electro-optical glazing structure comprising a PSCT liquid crystal material including a chiral liquid crystal and a monomer, the monomer lacking the mesogenic group of the general formula:



84. (Amended) A liquid crystal material for an electro-optical glazing structure comprising a chiral liquid crystal and Ethylene-ethylene Glycol-glycol Dimethacrylate-dimethacrylate (EGD) commercially available from Aldrich.

85. (Amended) A liquid crystal material for an electro-optical glazing structure comprising a chiral liquid crystal and a monomer selected from the group consisting of ethylene Glycol glycol Dimethacrylate dimethacrylate(EGD), urethane acrylates having a viscosity of about 300 to about 400 centipoise, and epoxies having a viscosity of about 1400 to about 1800 centipoise, Ethylene Glycol Dimethacrylate (EGD), UV10, UV15-7 and combinations comprising at least one of the foregoing monomers commercially available from Aldrich and Master Bond.

87. (Amended) The liquid crystal material of claim 86, wherein said dichroic dye is an anthraquinone dyeselected from the group consisting of D5, D35, D52 and combinations comprising at least one of the foregoing dyes commercially available from EMI.

88. (Amended) A liquid crystal material for an electro-optical glazing structure comprising a chiral liquid crystal, a monomer, and a surfactant.

REMARKS

Applicants thank the Examiner for the careful attention accorded this Application and respectfully requests reconsideration in view of the Amendments set forth above and the remarks below.

Claims 41, 46, 51, 56, 62, 83-85 and 88 have all been amended to more clearly define the liquid crystal material, such that the liquid crystal material generally includes a chiral liquid crystal material and a monomer (which is further limited in claims 41, 46, 51 and 83-85 as they stood prior to the amendment).

Claims 46 and 84 have also been amended to remove reference to the source of material. Claims 51 and 85 have been amended to replace the trade names of the monomers with readily known property parameters of the previously identified materials. Corresponding amendment to the specification has also been presented, and an attachment from Master Bond (www.masterbond.com/sg/uvsg.html) is included. Claims 61 and 87 have been amended to replace the trade names of the dichroic dyes with known structural characteristics of the

previously identified materials. Corresponding amendment to the specification has also been presented, and an attachment from Bahadur, Liquid Crystals, Applications and Uses, Vol. 3, p. 73 © 1992 World Scientific.

Applicants have cancelled claims 68-82, and 90-92 without prejudice or disclaimer. Applicants reserve the right to file one or more continuation applicants herefrom in order to continue prosecution of the inventive subject matter of the cancelled claims.

The examiner has variously rejected all of the pending claims under 35 USC § 103(a). To establish a prima facie case of obviousness, three basic criteria must be met. First, there must be some suggestion or motivation, either in the references themselves or in the knowledge generally available to one of ordinary skill in the art, to modify the reference or to combine reference teachings. Second, there must be a reasonable expectation of success. Finally, the prior art reference (or references when combined) must teach or suggest all the claim limitations. The teaching or suggestion to make the claimed combination and the reasonable expectation of success must both be found in the prior art, and not based on applicants' disclosure. In re Vaack, 947 F.2d 488, 20 USPQ2d 1438 (Fed. Cir. 1991).


Claims 41 and 83 have been rejected under 35 USC § 103(a) over McLaughlin et al. U.S. Patent No. 4,749,261 and Khan et al. U.S. Patent No. 6,172,720.

First, Applicants respectfully submit that there is no suggestion or motivation to combine the teachings of McLaughlin, which discloses privacy or solar control panels, with Khan, which discloses materials for liquid crystal displays, other than in Applicant's disclosure.

Second, even if the references were properly combinable, Applicants respectfully submit that all of the limitations of claims 41 and 83 are not taught or suggested in the references.

Particularly, claims 41 and 83 are directed, in part, to:

"...monomer lacking the mesogenic group of the general formula:



While the Examiner notes that Khan discloses a material having no liquid crystalline phase for the purpose of lowering viscosity of the material, the general formula $[\text{Si}(\text{CH}_3)\text{O}]_n$ is not taught or suggested. Therefore, it is respectfully submitted that claims 41 (and 42-45 which depend from claim 41) and claim 83 are patentable over the cited art.

Claims 46, 51, 84 and 85 stand rejected under 35 USC § 103(a) over McLaughlin et al. U.S. Patent No. 4,749,261 in view of Tangney U.S. Patent No. 4,961,532. It is respectfully submitted that there is no suggestion or motivation to combine the teachings of McLaughlin, which discloses privacy or solar control panels, with Tangney, which discloses materials for polymeric cosmetic carrier beads, and does not relate to or disclose use of the claimed materials including the monomers as liquid crystal materials for glazing structures.

Claims 56, 61, 86 and 87 stand rejected under 35 USC § 103(a) over McLaughlin et al. U.S. Patent No. 4,749,261 in view of Hakemi et al. U.S. Patent No. 6,049,366 and Cole Jr. U.S. Patent No. 4,097,130. It is respectfully submitted that there is no suggestion or motivation to combine the teachings of McLaughlin, which discloses privacy or solar control panels, and Hakemi, which discloses flexible polymer stabilized liquid crystal devices with Cole Jr., which discloses an actuatable multi-colored display using liquid crystal material including dichroic dye. In contrast, the dichroic dye is used in the present invention to impart to the electro-optical glazing structure a colored non-transparent state, and a tinted transparent state.

Claims 62 and 88 stand rejected under 35 USC § 103(a) over McLaughlin et al. U.S. Patent No. 4,749,261 in view of Simoni et al. U.S. Patent No. 4,579,422. It is respectfully submitted that the combination of the referenced does not disclose the features of the rejected claims. The use of a surfactant in Simoni is for the purpose of facilitating the mechanical rubbing step. In contrast, a surfactant is used in the invention of claims 62, 88 and claims depending therefrom for enhancing panel uniformity and decreasing flow streaks (specification, page 24, 4th paragraph).

Claims 67 and 89 stand rejected under 35 USC § 103(a) over McLaughlin et al. U.S. Patent No. 4,749,261 in view of Simoni et al. U.S. Patent No. 4,579,422 and Herb et al. U.S. Patent No. 6,022,547. First, the differences pointed out above with regard to Simoni obviate this rejection. Further, it is respectfully submitted that there is no suggestion or motivation to combine the teachings of McLaughlin, which discloses privacy or solar control panels, Simoni, which discloses continuously rotatable polarizing devices, and Herb, which discloses water-in-oil emulsions.


Claims 45, 50, 55 and 66, stand rejected under 35 USC § 103(a) over McLaughlin et al. U.S. Patent No. 4,749,261 in view of Hakemi et al. U.S. Patent No. 6,049,366. However, each of these claims are dependent claims, the parent claims of which have been addressed above. Further, the Examiner did not discuss the added features of claims 45, 50, 55 and 66 – using a float glass substrate. Hakemi discloses flexible substrates, thus the combination does not render the claimed inventions.

Claims 42-44, 47-89, 52-54, 57-59 and 63-65 stand rejected under 35 USC § 103(a) over McLaughlin and Khan, Tangney, Hakemi, Cole Jr. and Simoni as applied to claims 41, 46, 51, 56 and 62 further in view of Doane et al. U.S. Patent No. 5,691,785. However, each of these claims are dependent claims, the parent claims of which have been addressed above.

The amendments herein do not introduce any new matter. It is believed that the claims herein should be allowable to Applicants. Accordingly, allowance is respectfully requested.

Respectfully submitted,

Date: September 9, 2002
REVEO, INC.
85 Executive Boulevard
Elmsford, New York 10523
Telephone (914) 798-7270
Facsimile: (914) 345-9558

By: 
Ralph J. Crispino
Registration No. 46,144

MASTER BOND UV CURABLE PRODUCT SELECTOR GUIDE

Selected Master Bond UV Curable Adhesives, Sealants, Coatings & Encapsulants

Partial Listing Only - Other Grades Available

Master Bond Grade	Viscosity RT, cps	Color Code	Hardness Shore D	Service Temp Range, °F	Applications
UV10	300-400	light amber clear	60-65	-60 to 250°F	Low viscosity general purpose type adhesive, sealant, coating and encapsulant. Will cure rigid and up to 1/8" deep. Excellent resistance to water and other chemicals.
UV10FL	600-700	light amber clear	45-50	-60 to 250°F	Flexibilized version of UV10. Excellent resistance to mechanical shock and vibration. Superior thermal cycling properties. Well suited for bonding dissimilar substrates.
UV10LV	200	light amber clear	75	-60 to 250°F	Ultra-low viscosity adhesive, sealant, coating and encapsulant. Wickable. Outstanding electrical properties. Ideal for specialized conformal coating.
UV10MED	1,200-1,500	light amber clear	60-65	-60 to 250°F	Medical grade version of UV10. USP Class VI approved. Good physical strength properties and superior chemical resistance profile. Also serviceable as an encapsulant for medical electronics.
UV10PSA	16,000 & 25,000	transparent	N/A*	-60 to 250°F	High strength, fast tackling, pressure sensitive adhesive. Available in two different viscosities allowing for versatile application methods.
UV10TK	30,000-40,000	light amber clear	70-75	-60 to 300°F	Higher viscosity version of UV10. Enhanced temperature & chemical resistance. Good dimensional stability. Low shrinkage upon cure. Bonds well to most plastics, metals and glass.
UV11-3	60	transparent	N/A*	-60 to 260°F	Ultra-low viscosity, spin coatable, scratch resistant coating. Used with glass, acrylics, polycarbonates and other plastics.
UV14-3	25,000-30,000	transparent	20	-60 to 250°F	Flexible adhesive, sealant and encapsulant. Bonds well to a wide variety of substrates. Easily removable by conventional solvents. Possesses a very low index of refraction (1.45).
UV14X-2TK	bioluxotropic	transparent	60	-60 to 250°F	Semi-flexible adhesive, sealant and encapsulant. Exceptional durability. Superior electrical properties. Low shrinkage. Used in medical applications. Resists most chemical sterilants.
UV15	120-150	slight amber clear	N/A*	-60 to 350°F	Very low viscosity adhesive, sealant & coating. Features high temperature stability, superior chemical resistance as well as low shrinkage. Post curing by heat enhances properties.
UV15-12C	paste	translucent	60-70	-60 to 250°F	Ultra-fast curing, easy to handle adhesive/sealant. Superior dimensional stability. Low shrinkage. Widely used in opto-electronics. Convenient non-drip application feature.
UV15-7	1,400-1,800	transparent	65	-60 to 300°F	Excellent adhesive, sealant, coating and encapsulant. Cures over 1/8" deep. Superb non-yellowing properties. Unsurpassed electrical properties. Widely used in optical and electronic applications.
UV15-7DC	2,500-5,000	transparent	65-70	-60 to 300°F	Dual cure version of UV15-7. Will cure in shadowed cut areas by adding heat (250°F). Excellent physical and electrical properties. Bonds well to glass, metals and most plastics.

Master Bond Grade	Viscosity RT, cps	Color Code	Hardness Shore D	Service Temp Range, °F	Applications
UV15-7LR1	5,000-10,000	transparent	50	-60 to 250°F	Special low index of refraction (1.47). Used as an adhesive, sealant, and coating. Good mechanical properties. Primarily for optical and electro-optical applications. Superior thermal cycling properties. Highly flexibilized version of UV15-7. Outstanding thermal and mechanical shock resistance. Excellent thermal cycling capabilities. Unsurpassed non-yellowing properties.
UV15-7SR4	800-1,500	transparent	35	-80 to 250°F	Paste version of UV15-7. Good dimensional stability. Low shrinkage. Ideal for intricate sealing & bonding applications. Also used as an encapsulant & glob top in electronic & opto-electronics.
UV15-7TK1A	paste	translucent	65	-60 to 300°F	Flexible version of UV15. Enhanced peel strength. Bonds well to most metals, plastics & glass. Post curing by heat improves temperature and chemical resistance properties.
UV15FL	200-300	light amber clear	N/A*	-60 to 250°F	High viscosity version of UV15. Enhanced temperature resistance. Superior chemical resistance to acids, fuels and most solvents. Post curing with heat improves properties.
UV15TK	8,000-10,000	slight amber clear	N/A*	-60 to 350°F	Semi-flexible adhesive, sealant & encapsulant. Cures over 1/4" deep. Bonds very well to metals, most plastics & glass. Good electrical & non-yellowing properties. Ideal for bonding dissimilar substrates.
UV15X-2	6,000-8,000	transparent	65	-80 to 250°F	Easily processable glob top. Excellent moisture resistance. Combines superior durability, temperature resistance along with superb thermal cycling and shock resistance properties.
UV15X-2GT	paste	translucent	65	-80 to 250°F	Highly flexible adhesive, sealant & coating. Superior peel strength & abrasion resistance. Excels in withstanding shock, vibration & thermal cycling. Good electrical properties. Ideal for potting & encapsulation.
UV15X-6	120,000	transparent	30	-80 to 250°F	Medical grade version of UV15X-5. USP Class VI approved. Excellent adhesion to metals, plastics, glass and rubber. Good resistance to chemical sterilants.

*Shore D hardness can not be measured for this system

The cure speed of UV systems depends on depth of cure, the intensity of UV light source and the distance of the UV light source from the material being cured.

Master Bond UV products are specially packaged to protect them from UV light exposure. Store the product in its original container. Keep closed when not in use. Shelf life for most systems in original, unopened containers is 6 months in bottles or cans and 3 to 6 months in syringes depending on the product.

Master Bond Inc.

Adhesives, Sealants & Coatings • 154 Hobart Street • Hackensack, N.J. 07601 • Tel: 201-343-8983 • Fax: 201-343-2132

→ Notice: Master Bond believes the information on the data sheets is reliable and accurate as is technical advice provided by the company. Master Bond makes no warranties (expressed or implied) regarding the accuracy of the information and assumes no liability regarding the handling and usage of this product.

LIQUID CRYSTALS

Applications and Uses

Vol. 3

Edited by

Birendra Bahadur

Display Systems Engineering
Litton Systems Canada Ltd.
Etobicoke, Ontario M9W 5A7
Canada

© 1992

















World Scientific

Singapore • New Jersey • London • Hong Kong

11. Dichroic Liquid Crystal Displays 73

TABLE 2A: Examples of Various Types of Dichroic Dyes and Their Physical Parameters
ANTHRAQUINONE DYES (2.1 - 2.26), AZO DYES (2.27 - 2.31), OTHER TYPES (2.32 - 2.50)

Dye No.	Comm. Code	Structure / Name	λ_{max}	Order Parameter	Host (Solubility)
2.1	D16		596	0.65	E 7
2.2	D27		612	0.63	E 7
2.3				0.91	
2.4	D35		554	0.67	E 7
2.5	D43		557	0.68	E 7
2.6	D46		556	0.69	E 7
2.7	D52		546	0.65	E 7
2.8	D54		524	0.71	E 7
2.9	D77		558	0.68	E 7
2.10				0.80	ZLI 1132
2.11				0.90	ZLI 1132
2.12				0.85	ZLI 1132
2.13				0.71 0.76 0.78 0.31 0.52 0.56	E 7 E 43 ZLI 1691 MBBA EN 24 ROTN 101
2.14				0.66 0.68 0.65	E 7 E 43 EN 24

09/09/02 21:43:09

USPTO->

914 644 8939 RightFAX

Page 001

TO:Auto-reply fax to 914-644 8939 COMPANY:

Auto-Reply Facsimile Transmission



UNITED STATES
PATENT AND
TRADEMARK OFFICE

TO:

Fax Sender at 914 644 8939

Fax Information

Date Received:

9/9/02 9:34:53 PM [Eastern Daylight Time]

Total Pages:

20 (including cover page)

ADVISORY: This is an automatically generated return receipt confirmation of the facsimile transmission received by the Office. Please check to make sure that the number of pages listed as received in Total Pages above matches what was intended to be sent. Applicants are advised to retain this receipt in the unlikely event that proof of this facsimile transmission is necessary. Applicants are also advised to use the certificate of facsimile transmission procedures set forth in 37 CFR 1.8(a) and (b), 37 CFR 1.6(f). Trademark Applicants, also see the Trademark Manual of Examining Procedure (TMEP) section 306 et seq.

Received
Cover
Page

=====>

Monday, September 09, 2002 9:30 PM

Ralph J. Crispino 914 644 8939

p01

Revo-DIG2USAA/PM00

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT: Li et al.

SERIAL NO.: 09/287,570

FILING DATE: April 6, 1999

FOR: ELECTRO-OPTICAL GLAZING STRUCTURES AND
LIQUID CRYSTAL MATERIALS FOR USE THEREWITH

) Group Art Unit
) 2871
)
) Examiner:
) Z. Qi
)

Commissioner of Patents
Washington, D.C. 20231

TRANSMITTAL and EXTENSION FOR EXTENSION OF TIME

Sir:
Please find enclosed herewith a AMENDMENT AND RESPONSE TO OFFICE ACTION in response to the OFFICE ACTION in the instant application dated May 9, 2002.
Since this Response is filed within 3 months from the statutory period for response of three months, Applicants petition under the provisions of 37 CFR 1.136(a) to extend the period for filing a response to the above identified Amended. The requested extension is for 1 month from August 8, 2002 until September 8, 2002 (since September 8, 2002 was a Sunday). If an additional time extension is required, please consider this a petition therefore. Total time extension fees are \$55.00.

The total fee due of \$55.00 is to be paid as follows:

This Commission is hereby authorized to charge any fees which may be required or credit any overpayment, to Deposit Account No. 301045. A duplicate copy of this sheet is enclosed.
Respectfully submitted,

By:
Ralph J. Crispino
Registration No. 46,144

Date: September 9, 2002
REVCO, INC.
85 Executive Boulevard
Elmsford, New York 10523
Telephone (914) 791-7370
Facsimile (914) 343-9558

I hereby certify that this correspondence is being transmitted to the United States Patent and Trademark Office, located at 400 ...
Signature of Agent:
Date: 9/9/02
Name of Agent:
Name of Agent (Transmitting Paper):

- Received from 914 644 8939 at 09/09/02 9:34:53 PM [Eastern Daylight Time]

HP OfficeJet
Personal Printer/Fax/Copier/Scanner

Fax History Report for
Ralph J. Crispino
914 644-8939
Sep 09 2002 9:38pm

Last Fax

<u>Date</u>	<u>Time</u>	<u>Type</u>	<u>Identification</u>	<u>Duration</u>	<u>Pages</u>	<u>Result</u>
Sep 9	9:33pm	Sent	17038729318	5:19	20	OK

Result:

OK - black and white fax
OK color - color fax